



296110



Universal rotary dimmer (R, L, C, LED) with soft-lock, Light control

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage 230 V

Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

Fuse

- short-circuit and overload proof (electronic fuse)

Power

Dimmable conventional transformers 20 ... 420 VA

Loss power at full load ≈ 4 W

Electronic transformers 20 ... 420 W

Measurement

- with extension unit input for push-button (NO contact) with single-surface operation
- with input for extension units insert for universal rotary dimmer

Materials

Colour not applicable

Material Plastic/metal

Dimensions

Insertion depth 24 mm

Axis dimension Ø 4 mm

LED control

Dimmable 230 V retrofit LED lamps 3 ... 100 W

Incandescent bulbs control

230 V incandescent lamps and halogen lamps 20 ... 420 W

Installation, mounting

- with spreader claws

Connection

Conductor cross-section	0,5 ... 4 mm ²
Type of load	Universal and LED Retrofit
- with screw terminals	

Scope of delivery

- with incremental encoder

Equipment

- with brightness memory
- phase cut-on, cut-off or LED phase cut-on according to load type, self-learning

Use

- with soft-lock

Safety

Halogen free	yes
--------------	-----

Identification

Application, usage	Light control
Main design line	Light control